

F) Fisher Scientific

Part of Thermo Fisher Scientific

SAFETY DATA SHEET

Creation Date 08-Feb-2010 Revision Date 29-Oct-2014 Revision Number 1

1. Identification

Product Name Formaldehyde solution 37%

Cat No.: F79-1; F79-4; F79-4LC; F79-20; F79-200; F79-500; F79P-4; F79P-20

Synonyms Formalin; Methanal; Methylene oxide; Oxymethane; Formic aldehyde; Methyl aldehyde

Recommended Use Laboratory chemicals.

Uses advised against No Information available

Details of the supplier of the safety data sheet

Company Emergency Telephone Number

Fisher Scientific CHEMTREC®, Inside the USA: 800-424-9300
One Reagent Lane CHEMTREC®, Outside the USA: 001-703-527-3887

Fair Lawn, NJ 07410 Tel: (201) 796-7100

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 3 Acute oral toxicity Category 3 Acute dermal toxicity Category 3 Acute Inhalation Toxicity - Dusts and Mists Category 3 Skin Corrosion/irritation Category 1 Serious Eye Damage/Eye Irritation Category 1 Skin Sensitization Category 1 Carcinogenicity Category 1A Specific target organ toxicity (single exposure) Category 1 Target Organs - Respiratory system, Central nervous system (CNS), Optic nerve. Specific target organ toxicity - (repeated exposure) Category 1

Target Organs - Kidney, Liver, Heart, spleen, Blood.

Label Elements

Signal Word

Danger

Hazard Statements

Flammable liquid and vapor

Toxic if swallowed

Toxic in contact with skin

Toxic if inhaled

Causes severe skin burns and eye damage

May cause an allergic skin reaction

May cause cancer

Causes damage to organs

May cause respiratory irritation

May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing **Ingestion**

Rinse mouth

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

3. Composition / information on ingredients

Component	CAS-No	Weight %
Water	7732-18-5	45 - 48
Formaldehyde	50-00-0	37 - 40
Methyl alcohol	67-56-1	15

4. First-aid measures

Eye ContactRinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a

respiratory medical device. Immediate medical attention is required.

Ingestion Do not induce vomiting. Call a physician or Poison Control Center immediately.

Most important symptoms/effects Breathing difficulties. Causes burns by all exposure routes. May cause allergic skin

reaction. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle

pain or flushing

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable Extinguishing Media No information available

Flash Point 50 °C / 122 °F

Method - No information available

Autoignition Temperature

Explosion Limits

No information available

Upper
Lower
Sensitivity to Mechanical Impact
Sensitivity to Static Discharge
No data available
No information available
No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO2) Hydrogen Formaldehyde

Protective Equipment and Precautions for Firefighters

Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

HealthFlammabilityInstabilityPhysical hazards320N/A

6. Accidental release measures

Personal Precautions

Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional ecological

information.

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary **Up** measures against static discharges. Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling

Use only under a chemical fume hood. Remove all sources of ignition. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Flammables area.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Formaldehyde	Formaldehyde Ceiling: 0.3 ppm		IDLH: 20 ppm
			TWA: 0.016 ppm
			Ceiling: 0.1 ppm
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200 ppm	IDLH: 6000 ppm
	STEL: 250 ppm Skin		TWA: 200 ppm
			TWA: 260 mg/m ³
		(Vacated) STEL: 325 mg/m ³	STEL: 250 ppm
		Skin	STEL: 325 mg/m ³
		TWA: 200 ppm	
		TWA: 260 mg/m ³	

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Formaldehyde	Ceiling: 2 ppm	Ceiling: 2 ppm	STEL: 1.0 ppm
	Ceiling: 3 mg/m ³	Ceiling: 3 mg/m ³	CEV: 1.5 ppm
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm
	TWA: 262 mg/m ³	TWA: 260 mg/m ³	STEL: 250 ppm
	STEL: 250 ppm	STEL: 250 ppm	Skin
	STEL: 328 mg/m ³	STEL: 310 mg/m ³	
	Skin		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures

Use only under a chemical fume hood. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eveglasses or chemical safety googles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

Skin and body protection

Respiratory Protection

Wear appropriate protective gloves and clothing to prevent skin exposure. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Handle in accordance with good industrial hygiene and safety practice. **Hygiene Measures**

9. Physical and chemical properties

Physical State Liquid **Appearance** Colorless Odor pungent

Odor Threshold No information available No information available

Melting Point/Range 0 °C / 32 °F **Boiling Point/Range** 101 °C / 213.8 °F 50 °C / 122 °F **Flash Point**

Evaporation Rate No information available Flammability (solid,gas) No information available

Flammability or explosive limits

Upper No data available Lower No data available **Vapor Pressure** No information available

Vapor Density > 10

Relative Density No information available

Solubility Soluble in water Partition coefficient; n-octanol/water No data available **Autoignition Temperature** No information available No information available **Decomposition Temperature** No information available

Viscosity

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products. Heat, flames and sparks.

Incompatible Materials Strong oxidizing agents, Strong bases, nitriles, Acids, Isocyanates, Acid anhydrides,

Metals, Acid chlorides

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Hydrogen, Formaldehyde

Hazardous Polymerization Hazardous polymerization does not occur.

None under normal processing. **Hazardous Reactions**

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50 Category 3. ATE = 50 - 300 mg/kg. Category 3. ATE = 200 - 1000 mg/kg. **Dermal LD50**

Vapor LC50 Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information

Component LD50 Oral **LD50 Dermal** LC50 Inhalation

Formaldehyde	500 mg/kg (Rat)	270 mg/kg (Rabbit)	0.578 mg/L (Rat) 4 h
Methyl alcohol	6200 mg/kg (Rat)	Not listed	22500 ppm (Rat)8 h

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Causes burns by all exposure routes Irritation

Sensitization May cause sensitization by skin contact

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Water	7732-18-5	Not listed				
Formaldehyde	50-00-0	Group 1	Known	A2	Х	A2
Methyl alcohol	67-56-1	Not listed				

IARC: (International Agency for Research on Cancer)

NTP: (National Toxicity Program)

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program) Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human

Carcinogen

ACGIH: (American Conference of Governmental Industrial

Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mutagenic Effects Mutagenic effects have occurred in humans.

Reproductive Effects Experiments have shown reproductive toxicity effects on laboratory animals.

Developmental effects have occurred in experimental animals. Component substance is **Developmental Effects**

listed on California Proposition 65 as a developmental hazard.

Teratogenicity Teratogenic effects have occurred in experimental animals.

STOT - single exposure STOT - repeated exposure Respiratory system Central nervous system (CNS) Optic nerve

Kidney Liver Heart spleen Blood

No information available Aspiration hazard

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

No information available **Endocrine Disruptor Information**

Tumorigenic effects have been reported in experimental animals. See actual entry in Other Adverse Effects

RTECS for complete information.

12. Ecological information

Ecotoxicity

. Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Formaldehyde	Not listed	Leuciscus idus: LC50 = 15	Not listed	EC50 = 20 mg/L 96h
		ma/L 96h		EC50 = 2 mg/L 48h

	Methyl alcohol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
1	•		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	-
١				EC50 = 43000 mg/L 5 min	

Persistence and Degradability

No information available

Bioaccumulation/ Accumulation No information available.

Mobility

Component	log Pow
Formaldehyde	-0.35
Methyl alcohol	-0.74

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes	
Formaldehyde - 50-00-0	U122	-	
Methyl alcohol - 67-56-1	U154	-	

14. Transport information

DOT

UN-No UN1198

Proper Shipping Name FORMALDEHYDE, SOLUTIONS, FLAMMABLE

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group III

<u>TDG</u>

UN-No UN1198

Proper Shipping Name FORMALDEHYDE, SOLUTIONS, FLAMMABLE

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group III

<u>IATA</u>

UN-No UN1198

Proper Shipping Name FORMALDEHYDE, SOLUTIONS, FLAMMABLE

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group III

IMDG/IMO

UN-No UN1198

Proper Shipping Name FORMALDEHYDE, SOLUTIONS, FLAMMABLE

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group |||

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Water	Х	Χ	-	231-791-2	-		Х	-	Χ	Х	X
Formaldehyde	Х	Χ	-	200-001-8	-		Х	Χ	Х	Х	Х
Methyl alcohol	Х	Χ	-	200-659-6	-		Х	Χ	Х	Х	Х

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b)

Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Formaldehyde	50-00-0	37 - 40	0.1
Methyl alcohol	67-56-1	15	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Formaldehyde	X	100 lb	-	-

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Formaldehyde	X		-
Methyl alcohol	X		-

OSHA Occupational Safety and Health Administration Not applicable

Component	Specifically Regulated Chemicals	Highly Hazardous Chemicals
Formaldehyde	2 ppm STEL 0.5 ppm Action Level	TQ: 1000 lb
	0.75 ppm TWA	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Formaldehyde	100 lb	100 lb
Methyl alcohol	5000 lb	-

California Proposition 65

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Formaldehyde	50-00-0	Carcinogen	40 μg/day	Carcinogen
Methyl alcohol	67-56-1	Developmental	-	Developmental

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Formaldehyde	X	X	X	X	X

Methyl alcohol	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product contains the following DHS chemicals:

Component	DHS Chemical Facility Anti-Terrorism Standard
Formaldehyde	11250 lb STQ (solution)

Other International Regulations

Mexico - Grade Moderate risk, Grade 2

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class B3 Combustible liquid

D1A Very toxic materials D2A Very toxic materials D2B Toxic materials E Corrosive material



16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 08-Feb-2010

 Revision Date
 29-Oct-2014

 Print Date
 29-Oct-2014

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS)

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS